

MOLDED GEAR

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to a molded gear formed by cooling and solidifying a molten material such as a plastic, a metal and the like in a mold, and particularly, to a molded gear having a function as a cooling fan.

DESCRIPTION OF THE RELATED ART

30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
1130
1140
1150
1160
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340
1350
1360
1370
1380
1390
1400
1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560
1570
1580
1590
1600
1610
1620
1630
1640
1650
1660
1670
1680
1690
1700
1710
1720
1730
1740
1750
1760
1770
1780
1790
1800
1810
1820
1830
1840
1850
1860
1870
1880
1890
1900
1910
1920
1930
1940
1950
1960
1970
1980
1990
2000
2010
2020
2030
2040
2050
2060
2070
2080
2090
2100
2110
2120
2130
2140
2150
2160
2170
2180
2190
2200
2210
2220
2230
2240
2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370
2380
2390
2400
2410
2420
2430
2440
2450
2460
2470
2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
2610
2620
2630
2640
2650
2660
2670
2680
2690
2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840
2850
2860
2870
2880
2890
2900
2910
2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
3090
3100
3110
3120
3130
3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280
3290
3300
3310
3320
3330
3340
3350
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500
3510
3520
3530
3540
3550
3560
3570
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720
3730
3740
3750
3760
3770
3780
3790
3800
3810
3820
3830
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940
3950
3960
3970
3980
3990
4000
4010
4020
4030
4040
4050
4060
4070
4080
4090
4100
4110
4120
4130
4140
4150
4160
4170
4180
4190
4200
4210
4220
4230
4240
4250
4260
4270
4280
4290
4300
4310
4320
4330
4340
4350
4360
4370
4380
4390
4400
4410
4420
4430
4440
4450
4460
4470
4480
4490
4500
4510
4520
4530
4540
4550
4560
4570
4580
4590
4600
4610
4620
4630
4640
4650
4660
4670
4680
4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
4800
4810
4820
4830
4840
4850
4860
4870
4880
4890
4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010
5020
5030
5040
5050
5060
5070
5080
5090
5100
5110
5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
5250
5260
5270
5280
5290
5300
5310
5320
5330
5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480
5490
5500
5510
5520
5530
5540
5550
5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700
5710
5720
5730
5740
5750
5760
5770
5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920
5930
5940
5950
5960
5970
5980
5990
6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180
6190
6200
6210
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360
6370
6380
6390
6400
6410
6420
6430
6440
6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580
6590
6600
6610
6620
6630
6640
6650
6660
6670
6680
6690
6700
6710
6720
6730
6740
6750
6760
6770
6780
6790
6800
6810
6820
6830
6840
6850
6860
6870
6880
6890
6900
6910
6920
6930
6940
6950
6960
6970
6980
6990
7000
7010
7020
7030
7040
7050
7060
7070
7080
7090
7100
7110
7120
7130
7140
7150
7160
7170
7180
7190
7200
7210
7220
7230
7240
7250
7260
7270
7280
7290
7300
7310
7320
7330
7340
7350
7360
7370
7380
7390
7400
7410
7420
7430
7440
7450
7460
7470
7480
7490
7500
7510
7520
7530
7540
7550
7560
7570
7580
7590
7600
7610
7620
7630
7640
7650
7660
7670
7680
7690
7700
7710
7720
7730
7740
7750
7760
7770
7780
7790
7800
7810
7820
7830
7840
7850
7860
7870
7880
7890
7900
7910
7920
7930
7940
7950
7960
7970
7980
7990
8000
8010
8020
8030
8040
8050
8060
8070
8080
8090
8100
8110
8120
8130
8140
8150
8160
8170
8180
8190
8200
8210
8220
8230
8240
8250
8260
8270
8280
8290
8300
8310
8320
8330
8340
8350
8360
8370
8380
8390
8400
8410
8420
8430
8440
8450
8460
8470
8480
8490
8500
8510
8520
8530
8540
8550
8560
8570
8580
8590
8600
8610
8620
8630
8640
8650
8660
8670
8680
8690
8700
8710
8720
8730
8740
8750
8760
8770
8780
8790
8800
8810
8820
8830
8840
8850
8860
8870
8880
8890
8900
8910
8920
8930
8940
8950
8960
8970
8980
8990
9000
9010
9020
9030
9040
9050
9060
9070
9080
9090
9100
9110
9120
9130
9140
9150
9160
9170
9180
9190
9200
9210
9220
9230
9240
9250
9260
9270
9280
9290
9300
9310
9320
9330
9340
9350
9360
9370
9380
9390
9400
9410
9420
9430
9440
9450
9460
9470
9480
9490
9500
9510
9520
9530
9540
9550
9560
9570
9580
9590
9600
9610
9620
9630
9640
9650
9660
9670
9680
9690
9700
9710
9720
9730
9740
9750
9760
9770
9780
9790
9800
9810
9820
9830
9840
9850
9860
9870
9880
9890
9900
9910
9920
9930
9940
9950
9960
9970
9980
9990
10000

In recent years, many injection-molded plastic gears as molded gears are used in an OA system, an AV system, a electric/electronic system, an automobile part or the like. Such injection-molded plastic gear has a light weight and a self-lubricating property; generates a noise lower than that in a metal gear, and can be produced in bulk, leading to an economic advantage. Therefore, the injection-molded plastic gear has been utilized in a further widened range of application.

However, such injection-molded plastic gear has a relatively poor thermal conductivity and for this reason, heat is liable to be accumulated in the tooth faces and hence, the plastic gear has a characteristic that its mechanical nature is dependent on the heat.

In recent years, the OA system, the AV system or the like is designed at a reduced size, so that the space for accommodation of the gear is smaller, but also an unoccupied space is as small as possible. Therefore, even when the cooling of the part is required in the OA

system, the AV system or the like, a cooling fan cannot be disposed freely in some cases.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a molded gear having a function as a cooling fan, so that a forcible convection (flow of air) can be produced within a space having the molded gear accommodated therein.

To achieve the above object, according to a first aspect and feature of the present invention, there is provided a molded gear made with a plurality of teeth formed around an outer periphery thereof by cooling and solidifying a molten material in a mold, comprising a plurality of holes defined circumferentially in a portion radially inner than the teeth to extend through such radially inner portion from a surface to a back, and blades formed at side edges of the holes.

With such configuration, when the molded gear is rotated, a flow of air passed through the holes from the surface side to the back side of the molded gear can be generated by the blades and blown to a part such as an IC, a motor and the like disposed adjacent the molded gear to cool it, and heat-accumulated air around the IC, the motor or the like can be forcibly discharged to inhibit the rise in ambient temperature. Particularly, the molded gear according to the present invention has the fun function and hence, it is possible to supply air to an area where a fan cannot be specially placed, thereby cooling such area. In the molded gear according to the present

invention, the holes are defined adjacent the teeth and the blades
 are formed at side edges of the holes. In this case, the flow of
 air is produced by the blades to flow in the vicinity of the teeth,
 whereby the heat in the teeth and in the vicinity of the teeth can
 be taken away by the heat transfer and hence, the cooling of the teeth
 and an area in the vicinity of the teeth can be achieved effectively.

According to a second aspect and feature of the present invention,
 there is provided a molded gear made with a plurality of teeth formed
 around an outer periphery of a rim by cooling and solidifying a molten
 material in a mold, comprising a plurality of blades formed at distances
 circumferentially on an inner peripheral surface of the rim, and a
 radially inner portion formed on the side of inner peripheries of
 the blades to support the rim through the blades.

With such configuration, when the molded gear is rotated, the
 blades generate a flow of air directed from a surface to a back of
 the molded gear. As a result, a flow of air is along the inner peripheral
 surface of the rim is produced, and the heat of the teeth and the
 rim is taken away by such flow of air, whereby the teeth and the rim
 are cooled. Thus, a reduction in mechanical strength of the molded
 gear due to a rise in temperatures of the teeth and the rim is inhibited.
 In addition, according to the present invention, the axial flow of
 air produced by the blades is blown to another part disposed adjacent
 the molded gear and hence, the part disposed adjacent the molded gear
 can be cooled.

The above and other objects, features and advantages of the

invention will become apparent from the following description of the preferred embodiments taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1 is a front view of an injection-molded plastic gear according to a first embodiment of the present invention;

~~Fig.2 is a sectional view taken along a line A-A in Fig.1;~~

~~Fig.3 is a sectional view taken along a line B-B in Fig.1;~~

Fig.4 is a front view of an injection-molded plastic gear according to a second embodiment of the present invention;

~~Fig.5 is a sectional view taken along a line C-C in Fig.4;~~

~~Fig.6 is a sectional view taken along a line D-D in Fig.4;~~

Fig.7 is a front view of an injection-molded plastic gear according to a third embodiment of the present invention;

~~Fig.8 is a sectional view taken along a line E-E in Fig.7;~~

~~Fig.9 is a sectional view taken along a line F-F in Fig.7;~~

Fig.10 is an enlarged view of a portion of a rim; and

Fig.11 is a view showing a rim and a diametrical rib in connected states in which a disadvantage may be arisen.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will now be described by way of embodiments with reference to the accompanying drawings.

A first embodiment of the present invention will be first

Sub
A3

Sub
A4

FIG. 10

Sub
A5

Sub
A6

Sub
A7

Sub
A8

described.

Referring to Figs. 1 to 3, a gear 1 made of a plastic by an injection molding (which will be referred to as an injection-molded plastic gear hereinafter) is shown as a molded gear according to the present invention. The injection-molded plastic gear 1 according to the present embodiment includes a disk-shaped web 5 formed at an axially substantially central location around an outer periphery of a boss 4 having a shaft hole 3 into which a shaft 2 is fitted. Formed on each of opposite sides (a surface and a back) of the web 5 are a plurality of diametrical ribs 6 extending radiately from the outer periphery of the boss 4, and a substantially cylindrical circumferential rib 7 connecting the diametrical ribs 6 to one another in a circumferential direction. This ensures the reinforcement of the web 5 and provides a reduction in thickness of the web 5 and in its turn, a reduction in weight of the injection-molded plastic gear 1.

The injection-molded plastic gear 1 also includes a plurality of blades 8 formed at substantially equal distances around an outer periphery of the circumferential rib 7, and air-ventilating holes 10 each defined between the adjacent blades 8, 8, wherein each of the blades 8 forms a side edge of each hole 10 (see Figs. 1 and 3). In the injection-molded plastic gear 1, a rim 11 is formed around outer peripheries of the blades 8, and a plurality of teeth 12 are formed around an outer periphery of the rim 11, whereby a spur gear having a fan function is formed.

Each of the blades 8 is formed in such a manner that it is inclined

at a predetermined angle (θ) with respect to an axial direction, as shown in detail in Fig.3, and so that its end 8a on the side of the surface is located on an extension of the corresponding diametrical rib 6, and its end 8b on the side of the back is located between such diametrical rib 6 and the next diametrical rib 6 on the right side as viewed in Fig.1. Thus, when the injection-molded plastic gear 1 is turned in a counterclockwise direction as viewed in Fig.1 (in a direction indicated by an arrow), the blades 8 produce an axial flow of air passed from the surface side of the injection-molded plastic gear 1 through the holes 10 to the back side of the gear.

When the injection-molded plastic gear 1 having such arrangement is turned upon the transmission of a power, the flow of air passed through the holes 10 defined on the side of an inner periphery of the rim 11 is produced by the blades 8. Therefore, a heat accumulated in the teeth 12 and the rim 11 by the friction of tooth faces or the like is transferred to the flow of air, whereby the teeth 12 and the rim 11 are cooled. Thus, in the injection-molded plastic gear 1 according to the present embodiment, a reduction in mechanical strengths such as fatigue strength due to a rise in temperature of the teeth and the rim 11 can be suppressed to ensure the transmission of the power stable in a long period.

If a bearing, a motor or the like (not shown) generating a heat is disposed on the back of the injection-molded plastic gear 1 in Figs.1 and 3, then the flow of air produced by the blades 8 can be blown to the heat-generating source such as the bearing, the motor

or the like to cool the heat-generating source such as the bearing, the motor or the like and also to inhibit a rise in ambient temperature.

If an IC part (not shown) having a low degree of tolerance to heat is disposed on the back of the injection-molded plastic gear 1 in Figs. 1 and 3, then the flow of air generated by the blades 8 can be blown directly to the IC part to cool it, or the IC part can be protected from the heat by inhibiting the rise in ambient temperature, as described above.

The injection-molded plastic gear 1 having the fan function as described above exhibits a peculiar effect as described above, when it is accommodated in a small-sized casing for an OA system, an AV system or the like adjacent another part, and when it is difficult to provide a separate fan.

3A9 > In addition, in the present embodiment, it is unnecessary to place a separate fan, because the injection-molded plastic gear 1 has the fan function, and hence, it is possible to reduce the number of components for an OA system, an AV system or the like in which the injection-molded plastic gear 1 is provided to provide a reduction in price of an article such as the OA system, the AV system and the like and also to provide a reduction in size of the OA system, the AV system or the like.

In the present embodiment, the end of each of the blades 8 on the side of the surface is located on the extension of the corresponding diametrical rib 6 and hence, the flowing of the plastic (a molten material) during the injection molding is smooth and thus, a molding

failure is difficult to arise.

Figs.4 to 6 show a gear 1 made of a plastic by an injection molding as a molded gear according to a second embodiment of the present invention. As shown in Figs.4 to 6, the injection-molded plastic gear 1 according to the second embodiment includes a disk-shaped web 5 formed at an axially substantially central location around an outer periphery of a boss 4 having a shaft hole 3 into which a shaft 2 is fitted. Formed on each of opposite sides (a surface and a back) of the web 5 are a plurality of diametrical ribs 13 extending radiately from the outer periphery of the boss 4, and a substantially cylindrical circumferential rib 7 connecting the diametrical ribs 13 to one another in a circumferential direction. This ensures the reinforcement of the web 5 and provides a reduction in thickness of the web 5 and in its turn, a reduction in weight of the injection-molded plastic gear 1.

The injection-molded plastic gear 1 also includes a plurality of blades formed at substantially equal distances around an outer periphery of the circumferential rib 14, and air-ventilating holes 16 each defined between the adjacent blades 15, 15, wherein each of the blades 15 forms a side edge of each hole 16 (see Figs.4 and 6). In the injection-molded plastic gear 1, a circumferential rib 17 is formed around outer peripheries of the blades 15, and a web 18 is formed at a tooth-wise substantially central portion around an outer periphery of the circumferential rib 17. Diametrical ribs 20 are formed on opposite sides of the web 18. As a result, the web 18 is

reinforced by the circumferential rib 17 and the diametrical ribs 20. A rim 21 is formed around outer peripheries of the diametrical rib 20 and the web 18, and a plurality of teeth 22 are formed around an outer periphery of the rim 21. Thus, the injection-molded plastic gear 1 is formed as a spur gear having a fan function.

Each of the blades 15 is formed in such a manner that it is inclined at a predetermined angle (θ) with respect to an axial direction, as shown in detail in Fig. 6, and so that its end 15a on the side of the surface is located on an extension of the corresponding diametrical rib 13, and its end 15b on the side of the back is located between such diametrical rib 13 and the next diametrical rib 13 on the right side as viewed in Fig. 4. Thus, when the injection-molded plastic gear 1 is turned in a counterclockwise direction as viewed in Fig. 4, the blades 15 produce an axial flow of air passed from the surface side of the injection-molded plastic gear 1 through the holes 16 toward the back side.

In the injection-molded plastic gear 1 having such arrangement, the blades 15 are formed at radially inner positions more spaced apart from the rim 21, as compared with those in the first embodiment. Therefore, it is difficult to cool the rim 21 and the teeth 22 directly by a flow of air produced by the blades 15, but the flow of air produced by the blades 15 can be blown to the other parts disposed adjacent the injection-molded plastic gear 1 to cool them, and also to inhibit a rise in ambient temperature by the cooling the other parts.

In the present embodiment, the rim 21 is supported by the web

[illegible]

Even with the injection-molded plastic gear 1 having such arrangement, an effect similar to that in each of the first and second embodiments can be provided.

In the injection-molded plastic gear 1 according to the present embodiment, the diametrical ribs 23 extend from the boss 4 to the rim 11, and the hole 25 is defined between the adjacent diametrical

ribs 23, 23. Therefore, the rigidity of the plastic gear 1 can be enhanced more than those in the first and second embodiments.

In each of the above-described embodiments, the shape of the blades 8, 15, 26, the inclination angle of the blades 8, 15 and the size of the holes 10, 16, 25 are determined properly depending on the service conditions and the like of the injection-molded plastic gear 1.

Although the injection-molded plastic gear 1 as a molded gear has been described as an example in each of the above-described embodiments, the present invention is not limited to such plastic gear 1 and is applicable to a gear formed of a metal such as a magnesium alloy, an aluminum alloy and the like by a die-casting. The metal gear has a good thermal conductivity and hence, a heat is difficult to be accumulated in teeth. In addition, the mechanism strength of the metal gear is not dependent on heat, unlike the plastic gear, and hence, the metal gear has a large effect that a flow of air can be blown to a part disposed adjacent the teeth to cool it by an effect of cooling the teeth.

As described above, the molded gear is produced by cooling and solidifying the molten material such as the plastic and the metal in the mold and hence, even the complicated shapes of the holes 10, 16 and the blades 8, 15, 26 can be formed easily and accurately. Therefore, according to each of the above-described embodiments, the gear having the fun function can be produced in bulk and at a low cost.

The embodiments haven been described by way of the spur gear, but the present invention is not limited to it, and is applicable to a helical gear and another power-transmitting gear.

When the outer peripheral end of a diametrical rib 27 is connected to the inner peripheral surface 28a of a rim 28, the diametrical rib 27 is connected to the inner peripheral surface 28a of the rim 28 at a location corresponding to each of teeth 30, as shown in Fig.10. This is because if the diametrical rib 27 is connected to the inner peripheral surface 28a of the rim 28 at a location corresponding to a tooth root 31, as shown in Fig.11, the falling of the teeth 30 as shown by dashed lines in Fig.11 occurs, resulting in a degraded accuracy of formation of the teeth 30.

When the molded gear is formed in the form of a helical gear, blades are formed on the inner peripheral surface 28a of the rim 28 at locations corresponding to the teeth 30, as shown in Fig.10. Namely, in the helical gear, the blades are formed along the torsion of the teeth 30, whereby the falling of the teeth 30 as shown by dashed lines in Fig.11 can be prevented, leading to an enhanced accuracy of formation of the teeth 30.

In addition, the web 5, 18 is formed so that it is located at the axially substantially central portion of the boss 4 in each of the above-described embodiments, but the present invention is not limited to such arrangement of the molded gear and is applicable to a molded gear in which the web 5, 18 is formed at the axial end of the boss 4, and the rim 11, 21 is supported in a cantilever manner

on the web 5, 18, and to a molded gear of another structure. Thus, the present invention is applicable widely to a molded gear having a structure provided with air-ventilating holes made to extend through a portion radially inner than the teeth from the surface to the back, and blades for producing a flow of air passed through such air-ventilating holes.

The injection-molded plastic gear 1 according to each of the embodiments is designed so that when it is rotated in the counterclockwise direction, the blades 8, 15, 26 produce the flow of air directed from the surface side to the back side of the injection-molded plastic gear 1, as shown in Figs. 1, 4 and 7. However, when the injection-molded plastic gear 1 is rotated in a clockwise direction, the blades 8, 15, 26 may be formed so that they are inclined in a direction opposite from the direction of inclination of the blades 8, 15, 26 shown in Figs. 1, 4 and 7, so that a flow of air directed from the surface side to the back side of the injection-molded plastic gear 1 is produced by the blades 8, 15, 26.

Each of the embodiments has been illustrated in which the boss 4 having the shaft hole 3 is formed at the central portion of the injection-molded plastic gear 1, but the present invention is not limited to the embodiments, and the shaft may be formed directly at the central portion of the injection-molded plastic gear 1.